

TA102 Duct Sealant



Special Characteristics

- Low VOC and low Odor
- Excellent workability.
- Non corrosive towards metals.
- Slump resistant.
- High solid content.
- Low shrinkage

Typical application

- Suitable on all types of HVAC duct system including sheet metal duct, duct board and flexible ducts, sealing of seam, spigot and flange joints in metal fabrications.

Product Description

TA102 Duct Sealant is a gray water-based duct sealant used in medium and high-pressure duct systems. TA102 is a special formulation which provides permanent flexibility, excellent water-resistance and superior sealing strength.

Packing

Packing	Color	Quantity/carton
600ml	White, Black, Grey etc.	20 sausages
300ml	White, Black, Grey etc.	24 cartridges
280ml	White, Black, Grey etc.	24 cartridges




HVAC duct system



HVAC duct system



HVAC duct system



HVAC duct system

Technical Data

Appearance	Paste
Density	1.63g/cm ³
Skin Time	7~10min
Curing time	3.5mm/24h
Elongation at break	250%
Application temperature range	5°C to 40°C
Service temperature range	-20°C to 75°C
Hardness Shore A	32

Storage

When stored in original unopened container at or below 32°C, and above freezing, acrylic sealant has a shelf life of 18 months from manufacturing date. Containers should always be kept sealed when not in use.

Note

- Keep out of reach of children. In case of contact with eyes, please rinse eyes with plenty of water and seek medical advice as soon as possible